# **Biological Indicator Incubator**

# Bit1000/Bit1000-S



# **Description:**

Bit1000/Bit1000-S is a sample incubation equipment based on film heating and PID automatic temperature control technology. Flexible independent timing and constant temperature function improve the efficiency of the laboratory work, which is the ideal equipment for biological indicators incubation.

### Features:

- Easy to set up and use, all information real-time display and showing set up operation, convenient to observe equipment running status.
- ♦ High temperature control precision.
- ♦ Wide time range from 1min to 99h59min.
- Up to 7groups samples can be incubated. Each group countdowns independently at a time.
- Temperature calibration function.
- Built-in software and hardware over-temperature protection device.

#### Parameters:

Project	Parameters			
Temp. setting range	0°C~100°C			
Timing range	1min ~ 99h59min/∞			
Display accuracy	0.1°C			
Heating time	≤12min(from 25°C to 100°C)*			
Power	150W			
Fuse	250V 3A Φ5×20			
Weight(kg)	2.5			

Project	Parameters			
Temp. control range	RT+5°C~100°C			
Temp. accuracy	≤±0.3°C*			
Temp. uniformity	≤±0.3°C*			
Auto running	Yes			
Voltage	AC220V or AC110V, 50/60Hz			
Dimension(mm)	260x195x150			

### Optional Blocks:

Туре	Capacity	Remark	Туре	Capacity	Remark
RC02 044 001	35x⊕9mm	Only for Bit1000	RC02 044 002	35x⊕10mm	Only for Bit1000
RC02 044 003	28x⊕12mm	Only for Bit1000-S			

