

Description:

- The DC10 Chilling/Heating Dry Bath is compact, versatile, reliable ◆ and easy to use. It is adopted high quality Peltier plate to ensure long-term stable operation and controlled can be widely used in preservation and reaction of samples, DNA amplification, electrophoresis denaturation and serum solidification, etc. Applications:
- Maintaining 14°C for ligation reactions.
- Maintaining 17°C for storing oocytes.
- Storing samples at ice bucket temperatures.
- Storing enzymes or DNA libraries at your work station.
- Transporting samples from the field at exactly the right temperature.
- Chilling or heating samples in the field.
- Enzyme reactions and deactivations.
- Freezing and storing most any small sample at your work station.
- PCR sample preparation.

Features:

- Energy-efficient Peltier design.
- Automatic fault detection and buzzer alarm function.
- ${\bf Electronic\ calibration.\ User\ can\ reset\ to\ any\ local\ standard.}$
- Small, compact size uses very little bench space.
- Easy replacement, cleaning and disinfecting of metal blocks.
- Built-in over-temperature protection.
- Internal power supply provided is UL, CSA and CE approved.
- Customed modules are accepted.
- Buzzer alarm when temperature control ends.
- 12-month warranty.

Parameters:

Project	Parameters	
Temp setting range	-10°C~100°C	
Time range	1min ~ 99h59min/∞	
Display accuracy	0.1°C	
Heating time	≤10 min (from 25°Cto100°C)*	
AUTO-4°C	Yes*	
Multi points running	Yes(Max 5 points)	
Auto running	Yes	
Auto resume to run	Yes	
Power input	AC110~220V/50-60HZ	
Size(mm)	260x195x150 mm	
Test condition: Rt 25°C±2°C,block is 1.5ML*35,use mercurial thermometer, accuracy is ±0.1°C.		

Test condition: Rt 25°C±2°C,block is 1.5ML*35,use mercurial thermometer, accuracy is ±0.1°C.
Ontional Blocks:

Optional Blocks.		
Туре	Test tube and aperture	
MD30	96×0.2ml	
MD31	54×0.5ml	
MD32	35×1.5ml	
MD33	35×2.0ml	
MD34	15×0.5ml+20×1.5ml	

Project	Parameters
Temp control range	Below room temp 30°C~100°C
Temp accuracy	≤±0.3°C*
Temp uniformity	≤±0.3°C*
Cooling time	≤10min (from 100°C to 25°C)*
Cooling time	≤25min(from room temp to blow it 30°C)*
Multi cycle	Yes(Max 99 times)
Auto heating	Yes
Power	150W
Fuse	250V 3A Φ5×20
Weight	4.5Kg

Туре	Test tube and aperture
MD35	96×0.2ml(elisa plate)
MD36	24×5ml
MD37	15×10ml
MD38	12×15ml
MD39	6×50ml

