

Description:

DH100 series high temperature dry bath incubator controlled • Real-time temperature display, the countdown display. by microcomputer, use of high purity aluminum material as a ◆ Convenient module replacement, easy to clean and heat conduction medium instead of the conditional water bath device. which is easy to use, wide temperature range, high precision and etc. Can be widely used in the sample preservation, reaction of DNA amplification, electrophoresis, • Temperature deviation calibration function. degeneration, solidification and other kinds of serum biochemical sample thermostatic incubation process.

Features:

- Automatic fault detection and alarm function.
- ◆ Built-in over temperature protection device.

Parameters:

Project	Parameters
Temp.Range	RT.+5C -160°C
Temp uniformity	±0.5°C
Display accuracy	0.1°C
Heating time	≤15 min (25°Cto160°C)
Max power	300W
Size(mm)	260×220×100

Project	Parameters
Temp accuracy	±0.5°C (@40°C)
Temp accuracy	±1°C (@120°C)
Time range	1-99h59min/∞
Block quantity	1
Voltage	220V 50/60Hz
Weight(kg)	5.0

Optional Blocks:

Туре	Diameter of test tube	Number of test tube
MD01	6mm	48
MD02	7mm	48
MD03	10mm	24
MD04	12mm	24
MD05	13mm	24
MD06	15mm	16
MD07	16mm	16
MD08	19mm	12

Туре	Diameter of test tube	Number of test tube
MD09	20mm	12
MD10	26mm	8
MD11	28mm	4
MD12	40mm	3
MD13	0.2ml centrifuge tube	48
MD14	0.5ml centrifuge tube	48
MD15	1.5ml centrifuge tube	24
MD16	2.0ml centrifuge tube	24

