## Mini Thermal Cycler MTC3200



## **Description:**

MTC3200 Mini Thermal Cycler is a compact, accurate and economical thermal cycler, designed to fit lab's basic thermal cycling needs. The operation of the thermal cycler is controlled by a 5-inch color touch screen. It has a capacity for 32x0.2ml tubes. The wells are arranged in a 4x8 format, allowing the block to accept strips of 8 as well as individual tubes. Excellent block uniformity ensures consistency sample to sample. Fast incubation function meets the experimental needs of denaturation, enzyme digestion/enzyme linkage, ELISA, etc. With a small footprint, the Mini Thermal Cycler will fit almost anywhere.

## **Features:**

- Capacity: 32x0.2ml tubes and 4x8 tube strips.
- Heating/cooling method: Peltier.
- ◆ 5-inch intuitive color touch screen for easy programming of users.
- ◆ 100 typical programs can be stored in memory and easily recalled.
- The block heats and cools very quickly at rates as fast as 4°C/sec.
- The heated lid is self adjusting the spring loaded platen in the lid comes firmly into contact with the tops of the tubes to prevent samples evaporation and condensation.
- Temperature of heated lid can be changed or the heating function of lid can be turned off.
- ◆ After a run, samples can be held at 4°C.
- An on-screen report is available at the completion of a run.

## Parameters:

Project	Parameters	Project	Parameters
Capacity	32x0.2ml tubes, 4x8 tube strips	Temp. accuracy/uniformity	≤±0.25°C/≤±0.25°C
Temp. setting range	0°C~100°C	Max. heating time	4°C/sec
Temp. control range	4°C~100°C	Max. cooling time	2°C/sec
Heated lid range	RT.+5°C~110°C, user adjustable	Temp. display resolution	0.1°C
Time increments/decrements	1~120s	Temp. control	Simulated sample or block
Temp. increments/decrements	0. 1°C~9.9°C	Display	5-inch color touch screen, 800x480 Pixel
Storage at 4°C	Yes	Communication interface	USB(1 port)
Program memory	100 programs	On-screen report	Yes
Power	200W	Voltage	AC100~240V, 50-60Hz
Fuse	250V 3A Φ5×20	Dimension(mm)	260x200x125
Weight(kg)	2.3		



Hangzhou Ruicheng Instrument Co., Ltd

ADD: Building E, No. 8 of Houshan Road, Yuhang District, Hangzhou City, Zhejiang Province, China TEL: 86-571-88630940 FAX: 86-571-85126370 Email: sales2@ruiwell.com http://www.ruiwell.net